

Technical information

ContraFlux FM^{GN}

ReadyMix



Technical Data

Density at 20°C	0.962 g/cm3
Viscosity at 20°C	26 mPas
ph-value at 20°C	11,6
Boiling temperature	-
Explosion risk	none
Solubility in water	unlimited
Application temperature	20 - 30°C
Application	pure
Storing frost-free	in original container
Waste key	07 06 04
WPC	1
Hazards classification	GHS 07
Signal word	Warning
Contains	5 - 10% amino-ethanol

Water based alkaline ReadyMix cleaning detergent

Cleans particularly colophonium and condensats from flux management systems quickly and thoroughly e.g. from stainless steel, aluminium, etc.

ReadyMix for the direct use in the cleaning system



Applications

Cleaning of:	
Colophonium flux	++*
Low voc flux	++*
Waterbased flux	++*
Solder paste (soldered)	++*
Oil/Grease	++*

Please note warnings in the Safety Data Sheet and on the product label!
For commercial use only!

Your ContraFlux FM supplier:

Process

 	AF-AirFlow systems
	PF-PulseFlow

Part No. 090624-RM 10 // Contents 10l

Part No. 090624-RM 25 // Contents 25l

Made in Germany

Part No. 090624-RM1000 // Contents 1000l

***++ = ideal for application, + = recommended, o = usable but not recommended, - = not recommended**
Note: The spreadsheet only shows a general overview of the cleaning media specifications. Rinsing with tap water with a too high lime concentration may cause lime residues after drying. Cleaning tests are reasonable and necessary to determine the optimum cleaner configuration. Such tests may be carried out directly at the **kolb** Demonstration Center in Willich / Germany or can be initiated by contacting one of our international subsidiaries.

Kolb Cleaning Technology GmbH
Karl-Arnold-Str. 12 · D - 47877 Willich
Further information: www.kolb-ct.com

Phone +49 (0) 2154 9479 - 38
Fax +49 (0) 2154 9479 - 47
e-mail info@kolb-ct.com

All modifications due to technical improvements are subject to change without notice.