

Technical information

MultiEx A12[®]

ReadyMix



Technical Data

Density at 20° C	0,99 g/cm ³
Viscosity at 20° C	30 mPas
ph-value at 20°C	12,3
Boiling temperature	> 100° C
Explosion risk	none
Application temperature	20 - 45°C
Application	pure
Storing frost-free	in original container
Disposal by EAK-No.	07 06 04
WPC	1
VBF-classification	not applicable with this product

Water based alkaline broadband-cleaning ReadyMix

Cleans colophonium and flux quickly, thoroughly and with best material protection e.g. from mounted PCBs, Misprints, solder frames/solder carriers, machinery parts, magazines, aluminium, stainless steel, etc.

ReadyMix for direct use in the cleaning system

Subject to regulations EG 648/2004 VO the product contains detergents: alkylglycoethers, alkalines, multivalent alcohols, builders and sequestering agents

Applications



Cleaning of:	
SMD adhesive	+*
Solder paste	++*
Low voc flux	++*
Colophonium flux	++*
Waterbased flux	++*
Solder paste (soldered)	++*
Oil/Grease	++*

Please be aware: The product may irritate mucuous membrane, skin and eyes!

For commercial use only!

Your MultiEx A12 supplier:

Process

 	PowerSpray Systems
	AirFlow Systems

Part No. 090607-RM25 // Contents: 25 l

Part No.

Made in Germany

Part No.

***++ = ideal for application, + = recommended, o = usable but not recommended, - = not recommended**

Note: The spreadsheet only shows a general overview of the cleaning media specifications. Rinsing with tap water with a too high lime concentration may cause lime residues after drying. Cleaning tests are reasonable and necessary to determine the optimum cleaner configuration. Such tests may be carried out directly at the **kolb** Demonstration Center in Willich / Germany or can be initiated by contacting one of our international subsidiaries.

W. Kolb Fertigungstechnik GmbH
 Karl-Arnold-Str.12 · D - 47877 Willich
 Further information: www.kolb-ct.com

Phone +49 (0) 2154 9479 - 38
 Fax +49 (0) 2154 9479 - 47
 e-mail info@kolb-ct.com

All modifications due to technical improvements are subject to change without notice.