


PULLER SETS



10 ton capacity Push-Puller® set – Contains three popular Power Team bar-type pullers in one versatile set, packed in a handy plastic storage case. Tools included permit damage-free pulling of gears, bearings, harmonic balancers, and other parts having tapped holes. Ideal for servicing off-road construction equipment and machinery.

Multi-purpose puller set – This new assortment of pulling tools gives you a wide range of job versatility. You get a 5 lb. slide hammer puller, hub puller, two sizes of Power Team Grip-O-Matic® jaw-type pullers, a bearing pulling attachment plus a cross-bar gear and pulley puller, all contained in a handy plastic storage case.

Lock-on, jaw-type puller set – Components can be assembled to create several versatile puller versions. The puller head is turned to securely lock the jaws onto the part being removed. Both a 2-way and 3-way puller head are included, plus three long-reach and three short-reach puller jaws in a plastic storage box. Easily removes gears, bearings and other press-fitted parts.

Order No.	Set Contents	Description																																
1180 10 ton Push-Puller® set, in plastic storage case. Wt., 25 lbs. 	927	10 Ton Push-Puller®; 8 ³ / ₈ " reach, 2 ¹ / ₄ " to 7 ¹ / ₄ " spread. Comes with 6 ³ / ₄ " puller legs, other leg sizes are available separately (See page 199).																																
	522	Gear and pulley puller; spread range when used with 1/2" cap screws: 2" to 7 ³ / ₄ ". Cap screws not included.																																
	7393	Gear and pulley puller with standard 5 ¹ / ₂ " forcing screw, plus special 13" forcing screw. Includes two hex head cap screws, 3/8"-16 x 3" long. Spread range: 1 ¹ / ₂ " to 4 ¹ / ₄ ".																																
1181 Multi-purpose puller set. Wt., 25 lbs. 	1177	Slide hammer puller with 5 lb. hammer, 2-way and 3-way heads. Reversible: either two or three jaws may be used to handle both "inside" and "outside" pulling jobs.																																
	7208	Hub puller. Includes a spare locknut which permits use with No. 1177 slide hammer.																																
	1023	2 ton combination 2- or 3-jaw Grip-O-Matic® puller. Has 3 ³ / ₈ " max. reach, 4 ³ / ₄ " max. spread.																																
	1027	5 ton combination 2- or 3-jaw Grip-O-Matic® puller. Has 5 ¹ / ₂ " max. reach, 7" max. spread.																																
	7393	Bar-type gear and pulley puller with 5 ¹ / ₂ " long screw. Includes two hex head cap screws, 3/8"-16 x 3" long. Spread range: 1 ¹ / ₂ " to 4 ¹ / ₄ ".																																
1182 Jaw-type puller set. Wt., 6.8 lbs. 	<table border="1"> <thead> <tr> <th rowspan="2">Puller Jaws Order</th> <th rowspan="2">Inside* Min. (in.)</th> <th colspan="2">2-Jaw</th> <th colspan="3">3-Jaw Spread</th> <th rowspan="2">Outside Min. (in.)</th> <th rowspan="2">Max. (in.)</th> </tr> <tr> <th>Max. (in.)</th> <th>Outside Min. (in.)</th> <th>Max. (in.)</th> <th>Inside* Min. (in.)</th> <th>Max. (in.)</th> </tr> </thead> <tbody> <tr> <td>44195</td> <td>1¹/₂</td> <td>4¹/₂</td> <td>3/4</td> <td>5</td> <td>1¹/₂</td> <td>4³/₄</td> <td>1</td> <td>4¹/₂</td> </tr> <tr> <td>44148</td> <td>2³/₄</td> <td>5¹/₂</td> <td>3/4</td> <td>7¹/₂</td> <td>3¹/₄</td> <td>6¹/₄</td> <td>1</td> <td>6¹/₄</td> </tr> </tbody> </table>		Puller Jaws Order	Inside* Min. (in.)	2-Jaw		3-Jaw Spread			Outside Min. (in.)	Max. (in.)	Max. (in.)	Outside Min. (in.)	Max. (in.)	Inside* Min. (in.)	Max. (in.)	44195	1 ¹ / ₂	4 ¹ / ₂	3/4	5	1 ¹ / ₂	4 ³ / ₄	1	4 ¹ / ₂	44148	2 ³ / ₄	5 ¹ / ₂	3/4	7 ¹ / ₂	3 ¹ / ₄	6 ¹ / ₄	1	6 ¹ / ₄
	Puller Jaws Order	Inside* Min. (in.)			2-Jaw		3-Jaw Spread					Outside Min. (in.)	Max. (in.)																					
			Max. (in.)	Outside Min. (in.)	Max. (in.)	Inside* Min. (in.)	Max. (in.)																											
44195	1 ¹ / ₂	4 ¹ / ₂	3/4	5	1 ¹ / ₂	4 ³ / ₄	1	4 ¹ / ₂																										
44148	2 ³ / ₄	5 ¹ / ₂	3/4	7 ¹ / ₂	3 ¹ / ₄	6 ¹ / ₄	1	6 ¹ / ₄																										

* Can be used for internal pulling tasks when used with a slide hammer.

